



ÅNGSLANG 560

ANVÄNDNINGSSOMRÅDE

Lämplig till mättad ånga

KONSTRUKTION

Invändigt slät tub av EPDM, textilarmering utvändig slät EPDM

FÄRG

Svart

TEMPERATUROMRÅDE

-40°C till +170°C

STANDARDLÄNGDER

40 meter dim 102 till 120 20/40 meter

Art.nummer	ID mm	YD mm	Vikt kg/m	A. tryck bar (20°)	S.tryck bar (20°)
560-08	8,0	18,0	0,23	8	50
560-10	10,0	21,0	0,31	8	50
560-12	12,0	23,0	0,35	8	50
560-13	13,0	24,0	0,38	8	50
560-15	15,0	26,0	0,42	8	50
560-16	16,0	27,0	0,44	8	50
560-18	18,0	30,0	0,54	8	50
560-19	19,0	31,0	0,55	8	50
560-20	20,0	33,0	0,63	8	50
560-22	22,0	35,0	0,68	8	50
560-25	25,0	37,0	0,68	8	50
560-30	30,0	45,0	1,02	8	50
560-32	32,0	47,0	1,08	8	50
560-35	35,0	50,0	1,16	8	50
560-38	38,0	54,0	1,36	8	50
560-40	40,0	56,0	1,42	8	50
560-45	45,0	64,0	1,93	8	50
560-51	51,0	68,0	1,89	8	50
560-60	60,0	82,0	2,89	8	50
560-70	70,0	86,0	2,31	8	50
560-80	80,0	100,0	3,34	8	50
560-90	90,0	112,0	4,18	8	50
560-102	102,0	120,0	3,80	8	50
560-120	120,0	140,0	4,96	8	50



ÅNGSLANG 560

ANVÄNDNINGSSOMRÅDE

Lämplig till mättad ånga

KONSTRUKTION

Invändigt slät tub av EPDM, textilarmering utvändig slät EPDM

FÄRG

Svart

TEMPERATUROMRÅDE

-40°C till +170°C

STANDARDLÄNGDER

40 meter dim 102 till 120 20/40 meter

Art.nummer	ID mm	YD mm	Vikt kg/m	A. tryck bar (20°)	S.tryck bar (20°)
560-08	8,0	18,0	0,23	8	50
560-10	10,0	21,0	0,31	8	50
560-12	12,0	23,0	0,35	8	50
560-13	13,0	24,0	0,38	8	50
560-15	15,0	26,0	0,42	8	50
560-16	16,0	27,0	0,44	8	50
560-18	18,0	30,0	0,54	8	50
560-19	19,0	31,0	0,55	8	50
560-20	20,0	33,0	0,63	8	50
560-22	22,0	35,0	0,68	8	50
560-25	25,0	37,0	0,68	8	50
560-30	30,0	45,0	1,02	8	50
560-32	32,0	47,0	1,08	8	50
560-35	35,0	50,0	1,16	8	50
560-38	38,0	54,0	1,36	8	50
560-40	40,0	56,0	1,42	8	50
560-45	45,0	64,0	1,93	8	50
560-51	51,0	68,0	1,89	8	50
560-60	60,0	82,0	2,89	8	50
560-70	70,0	86,0	2,31	8	50
560-80	80,0	100,0	3,34	8	50
560-90	90,0	112,0	4,18	8	50
560-102	102,0	120,0	3,80	8	50
560-120	120,0	140,0	4,96	8	50